

New Gen ASX (MY20)

Preliminary Specifications* (Europe – MME area)

	2.0 2WD M/T	2.0 2WD CVT	2.0 4WD CVT
Length	4,365 mm	4,365 mm	4,365 mm
Width	1,770 to 1,810 mm	1,770 to 1,810 mm	1,770 to 1,810 mm
Height	1,640 mm	1,640 mm	1,640 mm
Wheelbase	2,670 mm	2,670 mm	2,670 mm
Tracks (Fr / Rr)	1,525 mm / 1,530 mm or 1,545 mm / 1,545 mm	1,525 mm / 1,530 mm or 1,545 mm / 1,545 mm	1,525 mm / 1,530 mm or 1,545 mm / 1,545 mm
Ground clearance	190 mm	190 mm	190 mm
Approach angle	20.1°	20.1°	20.1°
Breakover angle	19.0°	19.0°	19.0°
Departure angle	31.4°	31.4°	31.4°
Towing capacity	1,300 kg	1,300 kg	1,300 kg
Curb weight	1,355 to 1,375 kg	1,385 to 1,405 kg	1,450 to 1,470 kg
Cargo volume (from / to)	406 l (5 passengers)	406 l (5 passengers)	406 l (5 passengers)
Turning radius	5.30 m	5.30 m	5.30 m

Fr. suspension	MacPherson struts	MacPherson struts	MacPherson struts
Rr. suspension	Multi-link	Multi-link	Multi-link
Brakes (Fr / Rr)	Vented discs (16") / discs	Vented discs (16") / discs	Vented discs (16") / discs
Wheels & Tires	215/70R16 or 225/55R18	215/70R16 or 225/55R18	215/70R16 or 225/55R18

Bore x stroke (displ.)	86 x 86 mm (1,998 cc)	86 x 86 mm (1,998 cc)	86 x 86 mm (1,998 cc)
Compression ratio	10.5	10.5	10.5
ps @ rpm	150 ps @ 6,000 rpm	150 ps @ 6,000 rpm	150 ps @ 6,000 rpm
Nm @ rpm	195 Nm @ 4,200 rpm	195 Nm @ 4,200 rpm	195 Nm @ 4,200 rpm
Fuel economy (combined)	n/a*	n/a*	n/a*
CO₂ emissions (combined)	n/a*	n/a*	n/a*
Max. speed**	190 km/h	190 km/h	190 km/h
0 – 100 km/h**	10"2	11"7	12"2
0 – 400m**	17"4	18"5	18"8
60 – 80 km/h**	6"6	3"8	4"0
120 – 140 km/h**	13"7	6"6	7"2

*Subject to final homologation

**where legal